

UC-408: OoO list

Table of contents

- [Used documentation](#)
- [General information](#)
 - [Restrictions](#)
 - [GetOoOList](#)
- [Basic flow](#)
- [Alternative flow 1](#)
- [Alternative flow 2](#)
- [Alternative flow 3](#)

Used documentation

Cookbook	Version	Location
eHealthBox v3 Consultation WS	3.2	https://www.ehealth.fgov.be/ehealthplatform/nl/service-beveiligde-elektronische-brievenbus-ehealthbox

General information

Restrictions

- A person cannot be defined as a substitute if he is already absent for this period (or part of the period).
- It is however possible to introduce an OoO while being a substitute for someone else.
- A person may be substitute for several other persons.
- The absent person and his substitutes are persons, not organizations.
- A person is identified by his ID and his quality.
- There may be maximum five substitutes per OoO.
- A maximum of ten periods OoO may exist per eHealthBox.
- OoO periods may not overlap.
- A period may not end later than J + 1 year.
- A period can last up to 1 year.
- The end date is mandatory.

A WS request contains one period and a maximum of five substitutes may be specified for that period.
The OoO activates automatically when the time is reached.

GetOoOList

The GetOoOList method is used to list all inserted OoO for the considered eHealthBox. The list contains all OoO: past, active and future OoO. The OoOid returned can further be used to delete an OoO.

Request


- [Example request](#)

Response

The response contains a success status code and as many OoO elements as there are OoO in the considered eHealthBox. Each element contains all OoO data when it was inserted.

- [Example response](#)

Basic flow

Flow	Specifications																						
<div>  Unknown macro: 'drawio' </div>	<table> <tr> <td>ID</td><td>UC408-BF</td></tr> <tr> <td>Name</td><td>Set an out-of-office with 1 substitute</td></tr> <tr> <td>Description</td><td>/</td></tr> <tr> <td>Actor(s)</td><td> Two healthcare professionals: <ul style="list-style-type: none"> One who will be OoO. One who will be the substitute. </td></tr> <tr> <td>Requirements</td><td>/</td></tr> <tr> <td>Trigger</td><td>A user wants to set an out-of-office.</td></tr> <tr> <td>Precondition (s)</td><td> <ul style="list-style-type: none"> The user is logged in. The user wants to set an out-of-office. </td></tr> <tr> <td>Flow</td><td> <ol style="list-style-type: none"> see Use case: login. When opening the OoO section, the application should automatically request a list of already inserted OoO periods. The inserted OoO period should be, for example, from the next monday until friday of the same week. Add the substitute (Example_Test_Actor). There are two ways to do this: <ul style="list-style-type: none"> Add the NISS number of the substitute manually. See Use case: Search healthcare professional </td></tr> <tr> <td>Postcondition (s)</td><td> <ul style="list-style-type: none"> The OoO is successfully added. There is one more OoO period than there was before the insert. </td></tr> <tr> <td>Test Data</td><td> GetOoOList <ul style="list-style-type: none"> Example request Example response InsertOoO <ul style="list-style-type: none"> Example request Example response </td></tr> <tr> <td>Endpoint(s)</td><td> <ul style="list-style-type: none"> ehBoxConsultation (https://services-acpt.ehealth.fgov.be/ehBoxConsultation/v3) </td></tr> </table>	ID	UC408-BF	Name	Set an out-of-office with 1 substitute	Description	/	Actor(s)	Two healthcare professionals: <ul style="list-style-type: none"> One who will be OoO. One who will be the substitute. 	Requirements	/	Trigger	A user wants to set an out-of-office.	Precondition (s)	<ul style="list-style-type: none"> The user is logged in. The user wants to set an out-of-office. 	Flow	<ol style="list-style-type: none"> see Use case: login. When opening the OoO section, the application should automatically request a list of already inserted OoO periods. The inserted OoO period should be, for example, from the next monday until friday of the same week. Add the substitute (Example_Test_Actor). There are two ways to do this: <ul style="list-style-type: none"> Add the NISS number of the substitute manually. See Use case: Search healthcare professional 	Postcondition (s)	<ul style="list-style-type: none"> The OoO is successfully added. There is one more OoO period than there was before the insert. 	Test Data	GetOoOList <ul style="list-style-type: none"> Example request Example response InsertOoO <ul style="list-style-type: none"> Example request Example response 	Endpoint(s)	<ul style="list-style-type: none"> ehBoxConsultation (https://services-acpt.ehealth.fgov.be/ehBoxConsultation/v3)
ID	UC408-BF																						
Name	Set an out-of-office with 1 substitute																						
Description	/																						
Actor(s)	Two healthcare professionals: <ul style="list-style-type: none"> One who will be OoO. One who will be the substitute. 																						
Requirements	/																						
Trigger	A user wants to set an out-of-office.																						
Precondition (s)	<ul style="list-style-type: none"> The user is logged in. The user wants to set an out-of-office. 																						
Flow	<ol style="list-style-type: none"> see Use case: login. When opening the OoO section, the application should automatically request a list of already inserted OoO periods. The inserted OoO period should be, for example, from the next monday until friday of the same week. Add the substitute (Example_Test_Actor). There are two ways to do this: <ul style="list-style-type: none"> Add the NISS number of the substitute manually. See Use case: Search healthcare professional 																						
Postcondition (s)	<ul style="list-style-type: none"> The OoO is successfully added. There is one more OoO period than there was before the insert. 																						
Test Data	GetOoOList <ul style="list-style-type: none"> Example request Example response InsertOoO <ul style="list-style-type: none"> Example request Example response 																						
Endpoint(s)	<ul style="list-style-type: none"> ehBoxConsultation (https://services-acpt.ehealth.fgov.be/ehBoxConsultation/v3) 																						

Alternative flow 1

Flow	Specifications
------	----------------



Unknown macro: 'drawio'

ID	UC408-AF01
Name	Set an out-of-office with 2 or more substitutes
Description	/
Actor(s)	Three or more healthcare professionals: <ul style="list-style-type: none">• One who will be OoO.• Two or more who will be substitutes.
Requirements	/
Trigger	A user wants to set an out-of-office.
Precondition (s)	<ul style="list-style-type: none">• The user is logged in.• The user wants to set an out-of-office.
Flow	<ol style="list-style-type: none">1. see Use case: login.2. When opening the OoO section, the application should automatically request a list of already inserted OoO periods.3. The inserted OoO period should be, for example, from the next monday until friday of the same week.4. Add the substitutes (Example_Test_Actor1) and (ExampleTest_Actor2). There are two ways to do this:<ul style="list-style-type: none">• Add the NISS number of the substitutes manually.• See Use case: Search healthcare professional
Postcondition (s)	<ul style="list-style-type: none">• The OoO is successfully added.• There is one more OoO period than there was before the insert.
Test Data	<p>GetOoOList</p> <ul style="list-style-type: none">• Example request• Example response <p>InsertOoO</p> <ul style="list-style-type: none">• Example request• Example response
Endpoint(s)	<ul style="list-style-type: none">• ehBoxConsultation (https://services-acpt.ehealth.fgov.be/ehBoxConsultation/v3)

Alternative flow 2

Flow	Specifications
------	----------------



Unknown macro: 'drawio'

ID	UC408-AF02
Name	Delete an out-of-office.
Description	/
Actor(s)	One healthcare professional
Requirements	/
Trigger	A user wants to delete an out-of-office.
Precondition (s)	<ul style="list-style-type: none">• The user is logged in.• The user has atleast one out-of-office period.• The user wants to delete an out-of-office.
Flow	<ol style="list-style-type: none">1. see Use case: login.2. When opening the OoO section, the application should automatically request a list of already inserted OoO periods.
Postcondition (s)	<ul style="list-style-type: none">• The OoO is successfully deleted.• There is one less OoO period than there was before the delete.
Test Data	<p>GetOoOList</p> <ul style="list-style-type: none">• Example request• Example response <p>DeleteOoO</p> <ul style="list-style-type: none">• Example request• Example response
Endpoint(s)	<ul style="list-style-type: none">• ehBoxConsultation (https://services-acpt.ehealth.fgov.be/ehBoxConsultation/v3)

Alternative flow 3

Flow	Specifications
------	----------------



Unknown macro: 'drawio'

ID	UC408-AF02
Name	Update an out-of-office.
Description	/
Actor(s)	One healthcare professional
Requirements	/
Trigger	A user wants to update an out-of-office.
Precondition (s)	<ul style="list-style-type: none">• The user is logged in.• The user has atleast one out-of-office period.• The user wants to update an out-of-office.
Flow	
Postcondition (s)	<ul style="list-style-type: none">• The OoO is successfully updated.
Test Data	<p>GetOoOList</p> <ul style="list-style-type: none">• Example request• Example response <p>InsertOoO</p> <ul style="list-style-type: none">• Example request• Example response <p>DeleteOoO</p> <ul style="list-style-type: none">• Example request• Example response
Endpoint(s)	<ul style="list-style-type: none">• ehBoxConsultation (https://services-acpt.ehealth.fgov.be/ehBoxConsultation/v3)