

UC-405: Move message

Table of contents

- Used documentation
- General information
 - MoveMessage
 - Request
 - Response
- Basic flow
- Alternative flow 1
- Exception flow 1
- Exception flow 2

Used documentation

Cookbook	Version	Location
eHealthBox v3 Consultation WS	3.2	https://www.ehealth.fgov.be/ehealthplatform/nl/service-beveiligde-elektronische-brievenbus-ehealthbox

General information

MoveMessage

The MoveMessage method enables the user to move a message from a Source (“INBOX”, “SENTBOX”, “BININBOX”, “BINSENTBOX”) to a Destination (“INBOX”, “SENTBOX”, “BININBOX”, “BINSENTBOX”). Only some combinations are allowed as explained below. You need to indicate if a message was received or sent by the concerned eHealthBox. You can do this by looking where the message is situated or compare the currently connected user and the Sender and/ or Destination element.

The following table displays the allowed combinations of the MoveMessage method:

Source	Destination
INBOX	BININBOX
SENTBOX	BINSENTBOX
BININBOX	INBOX
BINSENTBOX	SENTBOX

Request

In Source specify where the message is currently situated and in Destination where the message must be moved to. In MessageId specify as many elements as there are messages to be moved. This method can only move 100 messages at a time; consequently, you must use it multiple times if necessary.

- Example request

Response

The response contains a success status code or a Business Error as defined in Chapter 8. The Business Error enables you to identify which messages were not successfully moved, even though all other have been moved successfully.

- Example response
- Status codes

Basic flow

Flow	Specifications
 Unknown macro: 'drawio'	<p>ID UC405-BF</p> <p>Name Move a message from one message box to another message box from the message list view</p> <p>Description A 'message box' can be one of the following: inbox, sent box, bin inbox and in sent box. A table of allowed combinations can be found here.</p> <p>Actor(s) One healthcare professional</p> <p>Requirements <ul style="list-style-type: none"> ■ Atleast one message in one of the message boxes. </p> <p>Trigger A healthcare professional wants to move a message.</p> <p>Precondition(s) <ul style="list-style-type: none"> • The user is logged in. • The user wants to move a message. </p> <p>Flow <ol style="list-style-type: none"> 1. See use case: login. 2. The user wants to view the contents of one of his message boxes. The user will see a list with all of his message for the specific folder he/she requested. See use case: consultation for more information about the GetMessageList method. 3. The user selects a message. The user moves this message to a different message box. 4. The user gets automatically returned to the list view of the message box he /she was in. The list gets updated automatically. </p> <p>Postcondition(s) <ul style="list-style-type: none"> • The message is no longer available in the message box it was consulted in. • The message is available in the message box it was moved to. </p> <p>Test Data <p>GetMessagesList <ul style="list-style-type: none"> ■ Example request ■ Example response </p> <p>MoveMessage <ul style="list-style-type: none"> ■ Example request ■ Example response </p> </p> <p>Endpoint(s) <ul style="list-style-type: none"> • ehBoxConsultation (https://services-acpt.ehealth.fgov.be/ehBoxConsultation/v3) GetMessagesList MoveMessage </p>

Alternative flow 1

Flow	Specifications



Unknown macro: 'drawio'

ID	UC405-AF01
Name	Move a message from one message box to another message box from the full message view
Description	A 'message box' can be one of the following: inbox , sent box , bin inbox and in sent box . A table of allowed combinations can be found here .
Actor(s)	One healthcare professional
Requirements	<ul style="list-style-type: none"> ■ Atleast one message in one of the message boxes.
Trigger	A healthcare professional wants to move a message.
Precondition (s)	<ul style="list-style-type: none"> • The user is logged in. • The user wants to move a message.
Flow	<ol style="list-style-type: none"> 1. See use case: login. 2. The user wants to view the contents of one of his message boxes. The user will see a list with all of his message for the specific folder he/she requested. See use case: consultation for more information about the GetMessageList method. 3. The user selects one message to read. The message will be opened. See use case: read message for more information about the GetFullMessage method. 4. The user moves this message to a different message box. 5. The user gets automatically returned to the list view of the message box he /she was in. The list gets updated automatically.
Postcondition (s)	<ul style="list-style-type: none"> • The message is no longer available in the message box it was consulted in. • The message is available in the message box it was moved to.
Test Data	<p>GetMessagesList</p> <ul style="list-style-type: none"> • Example request • Example response <p>GetFullMessage</p> <ul style="list-style-type: none"> ■ Example request ■ Example response <p>MoveMessage</p> <ul style="list-style-type: none"> • Example request • Example response
Endpoint(s)	<ul style="list-style-type: none"> • ehBoxConsultation (https://services-acpt.ehealth.fgov.be/ehBoxConsultation/v3) <p>GetMessagesList GetFullMessage MoveMessage</p>

Exception flow 1

Flow	Specifications
 Unknown macro: 'drawio'	<p>ID UC405-EF01</p> <p>Name Try to move a message to a not allowed message box</p> <p>Description A 'message box' can be one of the following: inbox, sent box, bin inbox and bin sent box. A table of allowed combinations can be found here.</p> <p>Actor(s) One healthcare professional</p> <p>Requirements <ul style="list-style-type: none"> Atleast one message in one of the message boxes. </p> <p>Trigger A healthcare professional wants to move a message.</p> <p>Precondition(s) <ul style="list-style-type: none"> The user is logged in. The user wants to move a message. </p> <p>Flow <ol style="list-style-type: none"> See use case: login. The user wants to view the contents of one of his message boxes. The user will see a list with all of his message for the specific folder he/she requested. See use case: consultation for more information about the GetMessageList method. The user attempts to move this message to a not allowed message box. Example of not allowed combinations are (Inbox Sent box, An error message (Error ID: 812) is displayed to the user. The error message can, for example, be removed by pressing OK. </p>
	<p>Postcondition(s)</p> <ul style="list-style-type: none"> The user sees an error message relating to his/her issue. The ID of the error message is 812. The application keeps working as intended.
	<p>Test Data</p> <p>GetMessagesList <ul style="list-style-type: none"> Example request Example response </p> <p>MoveMessage <ul style="list-style-type: none"> Example request Example response </p>
	<p>Endpoint(s)</p> <ul style="list-style-type: none"> ehBoxConsultation (https://services-acpt.ehealth.fgov.be/ehBoxConsultation/v3) GetMessagesList MoveMessage

Exception flow 2

Flow	Specifications
------	----------------

Unknown macro: 'drawio'	
ID	UC405-EF02
Name	Try to move a message with an invalid message id
Description	/
Actor(s)	One healthcare professional
Requirements	<ul style="list-style-type: none"> Atleast one message in one of the message boxes.
Trigger	A healthcare professional wants to move a message.
Precondition(s)	<ul style="list-style-type: none"> The user is logged in. The user wants to move a message.
Flow	<ol style="list-style-type: none"> See use case: login. The user wants to view the contents of one of his message boxes. The user will see a list with all of his message for the specific folder he /she requested. See use case: consultation for more information about the GetMessageList method. The user attempts to move this message with an invalid id. An error message (Error ID: 813) is displayed to the user. The error message can, for example, be removed by pressing OK.
Postcondition(s)	<ul style="list-style-type: none"> The user sees an error message relating to his/her issue. The ID of the error message is 813. The application keeps working as intended.
Test Data	<p>GetMessagesList</p> <ul style="list-style-type: none"> Example request Example response <p>MoveMessage</p> <ul style="list-style-type: none"> Example request Example response
Endpoint(s)	<ul style="list-style-type: none"> ehBoxConsultation (https://services-acpt.ehealth.fgov.be/ehBoxConsultation/v3) GetMessagesList MoveMessage