UC-410: Delete OoO

Table of contents

- Used documentation
- General information
 - RestrictionsDeleteOoO
- Basic flow

Used documentation

Cookbook	Version	Location
eHealthBox v3 Consultation WS	3.2	https://www.ehealth.fgov.be/ehealthplatform/nl/service-beveiligde-elektronische-brievenbus-ehealthbox

General information

Restrictions

- · A person cannot be defined as a substitute if he is already absent for this period (or part of the period).
- It is however possible to introduce an OoO while being a substitute for someone else.
- A person may be substitute for several other persons.
- The absent person and his substitutes are persons, not organizations.
- · A person is identified by his ID and his quality.
- There may be maximum five substitues per OoO.
- A maximum of ten periods OoO may exist per eHealthBox.
- OoO periods may not overlap.
- A period may not end later than J + 1 year.
- A period can last up to 1 year.
- The end date is mandatory.

A WS request contains one period and a maximum of five substitutes may be specified for that period. The OoO activates automatically when the time is reached.

DeleteOoO

The DeleteOoO method is used to delete an OoO for the considered eHealthBox. In order to delete an OoO for another eHealthBox, BoxId can be used. The OoO Id must be specified. It can be retrieved from InsertOoO, in the Id element or from GetOoOList.

Request

One or more OoO's can be deleted by request.

· Example request

Response

The response is "Success" without further details if everything went right. Otherwise, the OoOld which could not be found, will be returned in the response as detailed below. All other OoO that were found were deleted.

Example response

http://wiki.ivlab.iminds.be

Basic flow

Flow	Specifications	
Unknown macro: 'drawio'	ID	UC-410-BF
	Name	Delete an out-of-office.
	Description	/
	Actor(s)	One healthcare professional
	Requirements	1
	Trigger	A user wants to delete an out-of-office.
	Precondition (s)	 The user is logged in. The user has atleast one out-of-office period. The user wants to delete an out-of-office.
	Flow	 see Use case: login. When opening the OoO section, the application should automatically request a list of already inserted OoO periods.
	Postcondition (s)	 The OoO is successfully deleted. There is one less OoO period than there was before the delete.
	Test Data	GetOoOList • Example request • Example response DeleteOoO • Example request • Example response
	Endpoint(s)	ehBoxConsultation (https://services-acpt.ehealth.fgov.be /ehBoxConsultation/v3)

http://wiki.ivlab.iminds.be Page 2 / 2